


AIRCRAFT PARKING/DOCKING CHART - ICAO

BUDAPEST TOWER	118.100
BUDAPEST GROUND	121.900
BUDAPEST APRON 1	131.550

BUDAPEST/LISZT FERENC
APRON 1

	BEARING STRENGTH
Apron 1	PCN 50/R/B/X/T
Taxiways: A1, B1, C, D	PCN 60/F/B/X/T
Taxiways: B2	PCN 75/F/B/X/T
Taxiway width: 23 m, exception A1: 19 m.	




INS COORDINATES FOR AIRCRAFT STANDS

1	N47 26 39.00, E019 13 23.08
2	N47 26 36.43, E019 13 25.06
3	N47 26 33.82, E019 13 26.98
4	N47 26 31.21, E019 13 28.88
5	N47 26 28.94, E019 13 30.54
6	N47 26 26.62, E019 13 32.25
25	N47 26 19.03, E019 13 33.69
26	N47 26 17.43, E019 13 33.81
27	N47 26 15.96, E019 13 34.84
107	N47 26 24.65, E019 13 31.38
108	N47 26 23.17, E019 13 31.34
109	N47 26 21.68, E019 13 31.30
R110	N47 26 22.73, E019 13 39.07
R111	N47 26 22.31, E019 13 39.92
R112	N47 26 21.55, E019 13 40.38
R113	N47 26 20.77, E019 13 41.63
R114	N47 26 20.43, E019 13 41.64
R115	N47 26 19.22, E019 13 43.91
R116	N47 26 16.33, E019 13 46.20
R117	N47 26 17.05, E019 13 46.32

ELEVATIONS ARE IN FEET AND DIMENSIONS IN METRES BEARINGS ARE MAGNETIC

SCALE 1 : 5 000



LIGHTING

TWY

- Taxiway edge: Low intensity omnidirectional blue.
- Taxiway centre line: Low intensity bi-directional green on taxiway B2.
- STOP bars: Unidirectional red.
- Apron: Low intensity red edge lights and floodlights.
- Obstacle light: Low intensity red.

FOR BASIC CHART SYMBOLS SEE: GEN 3.2. TAXI PROCEDURES SEE: AD 2-LHBP-MISC CHARTS.

APRON ELEVATION: NOT AVAILABLE. GEOGRAPHICAL COORDINATES FOR TWY CENTERLINES: NOT AVAILABLE. OBSTACLE TO TAXIING: NOT AVAILABLE.

THE PAGE INTENTIONALLY LEFT BLANK