


STANDARD ARRIVAL CHART -
INSTRUMENT (STAR) -
ICAO

TRANSITION ALTITUDE
9000

DEBRECEN TOWER	125,900
DEBRECEN INFO	125,900
BUDAPEST INFO (EAST)	133,000

DEBRECEN
RWY 05R / 23L
MARKA 5A PERIT 5A VERIG 5A



AD 2-LHDC-STAR

NAME	PROCEDURE	DESCENT	R/T FAILURE
PERIT 5A (22,2 NM)	After passing PERIT fly on track 160 (direction NARKA) and descend to FL 110. At DCN DME 12,2 NM descend to 5500 ft QNH. Proceed on track 160 and intercept bearing 211° inbound DC NDB. Descend to 5000 ft QNH after established inbound DC NDB.	When passing a fix, facility or waypoint, descent have to be initiated without delay to the lowest authorized level (depicted on the chart or by ATC) of the following segment.	If an arriving controlled aircraft experiencing R/T failure, it shall follow the STAR to 5000 ft QNH, fly a standard entry into the DC holding and 1 more holding pattern, after which a basic instrument approach procedure shall be initiated according to the known wind direction.
NARKA 5A (25,0 NM)	From NARKA proceed direction DC NDB on track 312. Cross DCN DME 11,4 NM between 9000 ft and 5000 ft QNH and turn left to join the DCN 10,0 NM DME arc. Proceed on the DME arc and at DC NDB QDM 001 turn right to intercept bearing 014° inbound DC NDB.		
VERIG 5A (23,0 NM)	From VERIG proceed direction DC NDB on track 335. Cross DCN DME 11,4 NM between 9000 ft and 5000 ft QNH and turn left to join the DCN 10,0 NM DME arc. Proceed on the DME arc and at DC NDB QDM 001 turn right to intercept bearing 014° inbound DC NDB.		

WAYPOINT COORDINATES
AD 2-LHDC-RNAV_(GNSS, DME/DME) STAR underlay

WAYPOINT	LATITUDE	LONGITUDE	WAYPOINT TYPE
DC001	N47 27 24.2	E021 33 46.9	FLY-BY
DC015	N47 35 51.1	E021 42 25.6	FLY-BY
DC016	N47 20 25.3	E021 43 45.6	FLY-BY
DC017	N47 19 09.5	E021 38 29.2	FLY-BY
DC018	N47 19 58.2	E021 30 08.1	FLY-BY

Straight segments shall be utilized through waypoints DC016 - DC017 - DC018 for the database coding of the conventional DME ARCs.